

SPEC SHEET

ASAPJ Serial no.990601

Neck: Laminate of quartersawn mahogany and flamed maple, scarf jointed at the headstock and glued into the body. The headstock is faced with Indian rosewood

Fingerboard: Selected quartersawn Indian rosewood and bone nut. Scale length is 650mm

Machines: Schaller M6 mini gold with pearl buttons.

Frets: 20 Van Gent#74 medium high, medium width, hard nickel silver.

Top: Bookmatched Engelmann spruce, hand graduated (2.7mm at bridge) and tap tuned. Bound in flamed maple and mulitply veneers. Bracing is of quartersawn spruce scalloped for lightness and response.

Back and Sides: Bookmatched Indian rosewood. Bound in flamed maple. Back bracing is quartersawn mahogany.

Bridge: Custom made Indian rosewood with compensated micarta saddle.

Finish: 15 coats of hand rubbed 2 pack, silk AC lacquer on back sides and neck. 20 coats of gloss AC lacquer on top and headstock.

Strings: D'Addario J17 13-56.

Pickup: Highlander piezo under saddle.

Switching: None

Circuitry: Highlander IP-1 preamp

Comments:. All woods specially selected for tonal quality and appearance. This guitar is not designed for strings stronger than 13 guage.

See note overleaf concerning climatic conditions and guitars.

This ASAP specially made by hand for my friends at PSS, Horten.